

Full Product Guide 2023



FRONTIER™ IF WE DON'T HAVE IT YOU PROBABLY DON'T NEED IT.



You, John Deere and Frontier. Let's work together.

Only Frontier's nearly 400 implements and attachments are designed, engineered, tested, and manufactured to fit and work seamlessly with John Deere tractors. That's a breadth and depth of equipment compatibility you won't find anywhere else in the world. Experience the fun, enjoyment and satisfaction you're looking for when working your land.

Engineered to work with John Deere tractors like no other implements in the world.





Full Product Guide

Contents

U.S.A. www.BuyFrontier.com

Canada www.BuyFrontier.ca

Landscape Equipment

Rear Blades • Box Blades • Land Planes • Landscape Rakes	2
Wood Chippers • Soil Pulverizers • Post Hole Diggers • 3-Point Trencher	3
Core Aerators • 3-Point Debris Blower • Material Collection System • Power Rakes	4

Tillage Equipment

Tandem Disks • Tandem Disk Harrow • One-Row Cultivator • Rotary Tillers	5
Plows • Field Cultivator • Subsoiler • Middle Buster	6

Seeding Equipme

Overseeders • Broadcast Spreaders • Pendular Spreaders • Conservation Seeders	7
---	---

Hay and Forage Equipment

Heavy-Duty Wheel Rake • High-Capacity Wheel Rakes • High-Capacity Carted Wheel Rakes • Carted Wheel Rakes	8
Hay Tedders • Disc Mowers • Disc Mower Caddy • Sickle Bar Mowers	9
Inline Bale Wrapper • 3-Point Bale Handling • Bale Spears • Round-Bale Hugger	10

Livestock and Equine Equipment

Hydraulic-Push Manure Spreaders • Chain-Unloading Manure Spreaders • Manure Forks • 3-Point Mounted Liquid Sprayers	11
---	----

Cutting and Mowing Equipment

Rotary Cutters • Grooming Mowers • Flex-Wing Grooming Mowers	14
--	----

Snow Removal Equipment

3-Point Snowblowers • Loader-Mount Snowblowers • Snow Pushes • Front Blades	15
---	----

Material Handling Equipment (Loader Attachments)

Loader Carrier Adapters • Pallet Forks • Mechanical Grapples • Pallet Fork Grapples	17
Root Grapples • Debris Grapples • Rock Buckets • Manure Forks	18
4-In-1 Buckets • Loader-Mount Rotary Brooms • Hydraulic Power Packs	19

Product Index

Product Index	20
---------------	----



Landscape Equipment



Rear Blades

Put your gardening, landscaping, driveway, and ditch-maintenance chores behind you with a sturdy Rear Blade.

Duty / Working Width	Engine HP ¹	Hitch
Economy – Heavy Plus 48 - 120 in. (121.9 - 304.8 cm)	19 - 160 hp (14.1 - 119.3 kW)	Ltd. Cat. 1, Cat. 1, 2 or 3

¹Reduce the hp requirement by 10 hp if the tractor has MFWD.



Box Blades

Frontier Box Blades level uneven ground and simplify grading tasks.

Working Width	Engine HP ¹	Hitch
48 - 97.5 in. (121.9 - 247.7 cm)	17 - 80 hp (12.8 - 59.6 kW) maximum	Cat. 0, Ltd. Cat. 1, or Cat. 1

¹Reduce the hp requirement by 10 hp if the tractor has MFWD



Land Planes

Level driveways, fill potholes, or recondition gravel areas with the all-purpose Land Planes. Durable frame allows you to smooth over challenging terrain. Heavy-duty options available.

Working Width	Engine HP	Hitch
48 - 120 in. (121.9 - 304.8 cm)	18 - 105 hp (13.4 - 78.3 kW)	Ltd. Cat. 1, Cat. 1 or 2

NEW LP21L & LP21 Series



Landscape Rakes

Cleaning up and grooming landscape is simple with a Landscape Rake. From debris and brush removal to surface leveling and final seed preparation, this attachment is up to the challenge of tough landscaping jobs.

Duty / Working Width	PTO HP	Hitch
Economy – Medium 48 - 96 in. (121.9 - 243.8 cm)	12 - 55 hp (8.9 - 41.0 kW)	Ltd. Cat. 1 or Cat. 1



Wood Chippers

Wood Chippers make big cleanup jobs fast and easy. They quickly chew up tree branches, turning them into wood chips or wood chip mulch.

Feed Opening	Limb	PTO HP	Hitch
3 x 5.5 - 5.5 x 8 in. (7.6 x 14.0 - 14.0 x 20.3 cm)	3 - 5 in. (7.6 - 12.7 cm)	18 - 95 hp (13.4 - 70.8 kW)	Cat. 1 or Cat. 2



Soil Pulverizers

Sod growers, landowners, landscapers, and contractors can prepare soil for seeding or sodding with a Soil Pulverizer.

Duty / Working Width	PTO HP	Scarifier Teeth	Hitch
Standard - Heavy 48 - 84 in. (121.9 - 213.4 cm)	30 - 70 hp (22.3 - 52.2 kW)	Bar Type	Cat. 1



Post Hole Diggers

Drill down quickly and deeply, on the farm or on the jobsite, with a Post Hole Digger.

Auger Length	PTO HP	Hitch
36 - 48 in. (91.4 - 121.9 cm)	15 - 90 hp (10.8 - 67.1 kW)	Cat. 1 or 2

NEW PDH05 Series



3-Point Trencher

Dig uniform trenches for any small drainage or utility project with the 3-Point Trencher. Just hitch up to a compact tractor and go.

Auger Length	PTO HP	Hitch
14 in. (35.6 cm)	15 - 30 hp (11.2 - 22.4 kW) Hydrostatic Transmission Only	Cat. 1

TipsNotebook.com

A compilation of tips, ideas & collective wisdom about how to get all kinds of jobs done around your place.



Core Aerators

Keep your lawn, park, or golf course healthy with a Core Aerator. These tools help reduce soil compaction, and promote air, water, and nutrient circulation.

Duty / Working Width	PTO HP	Hitch
Economy - Standard 48 - 72 in. (121.9 - 182.9 cm)	20 - 70 hp (14.9 - 52.2 kW)	Cat. 1 or 2

3-Point Debris Blower

Put the final touches on landscape projects with a 3-Point Debris Blower. It is ideal for quick cleanup of sidewalks, driveways, and golf courses.

PTO HP	Hitch
25 hp (18.6 kW) minimum	Cat. 1 and 2

Material Collection System

Attach the Frontier™ Material Collection System to your compatible John Deere drive over mower deck and make cleaning up grass clippings and leaves from your lawn easier than it's ever been.

Width	PTO Input	Hitch
60 in. (152.4 cm)	540 RPM	3-Pt. hitch, Cat. 1

NEW MC20 & MC21 Series

Power Rakes

Versatile Power Rakes make it fast and convenient to cultivate, level, grade, or restore soil surfaces.

Working Width	PTO HP	Hitch
Hydraulic 48 in. - 84 in. (121.9 cm - 213.4 cm)	15 hp - 80 hp (11.2 - 59.6 kW)	Cat. 1 or Cat. 2

You, John Deere and Frontier. Let's work together.

Tillage Equipment



Tandem Disks

When it's time to work your land, Frontier Disks are built to handle a variety of unpredictable soil conditions.

Working Width / Front / Rear Blade Spacing ¹	Engine HP	Disk Quantity
18 ft. (5.5 m) folding - 32 ft. (9.8 m) folding	160 - 180 hp (119.3 - 134.2 kW) - 280+hp (209+kW)	46 - 82



Tandem Disk Harrows

Breaking up tough ground calls for tough equipment. Like our Tandem Disk Harrows. Notched front blades are standard. Gang angles are easy to adjust requiring no tools.

Working Width / Front / Rear Blade Spacing ¹	Engine HP	Hitch
4 ft. (1.2 m) / 7.5 in. (19.1 cm) space - 8 ft. (2.4 m) / 9 in. (22.9 cm) space	14 - 28 hp (10.4 - 20.9 kW) - 40 - 75 hp (29.8 - 55.9 kW)	Cat. 1 ² or 2 ²

¹Front and rear spacing is identical. ²Match and/or Quick Hitch compatible.



One-Row Cultivator

Control weeds with the One-Row Cultivator. Adjustable row widths make this tool valuable for gardeners and small farm operators.

Row Width	PTO HP	Hitch
30 - 60 in. (76.2 - 152.4 cm)	18 - 45 hp (13.4 - 33.6 kW)	Cat. 1



Rotary Tillers

Put the final touches on gardens or seedbeds before planting with a Rotary Tiller.

Duty / Working Width ¹	Engine HP	Hitch
Standard - Heavy Duty 42 - 121 in. (106.7 - 307.3 cm)	15 - 120 hp (11.2 - 89.5 kW)	Ltd. Cat. 1, Cat. 1, or 2

NEW RT30 & RT30R Series

¹Regular and Reverse Tillers.



Plows

Prepare garden space or planting areas with One- and Two-Bottom Plows. Our 3-Point Plows allow you to turn over sod in your field or backyard.

Moldboard Width	PTO HP	Hitch
One - Bottom / 14 in. (35.6 cm) Two - Bottom / 40 in. (101.6 cm)	25 - 50 hp (13.4 - 37.3 kW)	Cat. 1

Field Cultivator

Prepare seedbeds, mix crop residue into soil, and blend soil to provide water and nutrients to crops with a versatile Field Cultivator.

Working Width	PTO HP	Hitch
72 in. (182.9 cm)	18 - 45 hp (13.4 - 33.6 kW)	Cat. 1

Subsoiler

This Subsoiler features a .750 x 4 in. (19.0 mm x 10.2 cm) steel shank with reversible point that rips through hard ground to break up compaction, improving water drainage and root growth.

Working Depth	PTO HP	Hitch
Up to 24 in. (61.0 cm)	18 - 45 hp (13.4 - 33.6 kW)	Cat. 1

Middle Buster

Break up hard ground between garden rows with a convenient Middle Buster with a 15 x 11 in. (38.1 x 27.9 cm) double-wing cutting blade.

Working Depth	PTO HP	Hitch
Up to 12 in. (30.5 cm)	18 - 45 hp (13.4 - 33.6 kW)	Cat. 1

TipsNotebook.com

A compilation of tips, ideas & collective wisdom about how to get all kinds of jobs done around your place.

Seeding Equipment



Overseeders

Get the lush, green turf you demand with a Frontier Overseeder. Perfect for property owners, golf courses, school systems, and municipalities.

Drive	Working Width	PTO HP	Hitch
Ground or PTO driven	Grnd, 48 - 84 in. (121.9 - 213.4 cm) PTO, 58 in. (147.3 cm)	Grnd, 25 - 125 hp (18.6 - 93.2 kW) PTO, 25 - 45 hp (18.6 - 33.6 kW)	Grnd, Ltd. Cat. 1, Cat.1 and 2 PTO, Cat.1



Broadcast Spreaders

Cover a lot of ground in a hurry with a Broadcast Spreader. These spreaders distribute fertilizer, salt, sand, small grains, and more.

Working Width	PTO HP	Hitch
20 - 49 ft. (6.1 - 14.9 m) swath	16 - 60 hp (11.9 - 44.7 kW)	Pull-type or Cat. 1



Pendular Spreaders

A precision Pendular Spreader provides uniform spreading, even if materials have different weights, sizes, and textures.

Working Width	PTO HP	Hitch
47 ft. (14.3 m) swath	20 - 60 hp (14.9 - 44.7 kW)	Cat. 1 or Cat. 2



Conservation Seeders

Renovate pastures or landscape roadsides with a Conservation Seeder. It makes quick work of any type of seeding, from native prairie grasses to large legumes.

Working Width	Drawbar HP	Hitch
5 - 7 ft. (1.5 - 2.1 m)	30 - 60 hp (22.4 - 44.7 kW) Minimum	Cat. 1 and 2



Hay and Forage Equipment



Heavy-Duty Wheel Rake

Rake more hay in less time with the Heavy-Duty Wheel Rake. Large, wind-panel rake wheels gather hay faster so you can start baling sooner.

Raking Width	Windrow Width	# of Wheels
29 ft. (8.8 m) maximum	72 in. (182.9 cm) maximum	17 Wheels



High-Capacity Wheel Rakes

High-Capacity Wheel Rakes give you the performance and consistency to engage nearly any type of terrain.

Raking Width	Windrow Width	# of Wheels
24 - 32 ft. (7.3 - 9.8 m) maximum	38 - 58 in. (96.5 - 147.3 cm)	12 - 16 Wheels



High-Capacity Carted Wheel Rakes

High-Capacity Carted Wheel Rakes provide fast raking speed without sacrificing performance to maximize hay quality and retain feed value.

Raking Width	Windrow Width	# of Wheels
19 - 24 ft. (5.79 - 7.3 m) maximum	36 - 72 in. (91.4 - 183 cm)	8 - 12 Wheels

NEW WR32 Series



Carted Wheel Rakes

Carted Wheel Rakes provide optimum maneuverability and extra down-pressure to adjust to land contours for tough raking jobs.

Raking Width	Windrow Width	# of Wheels
16 ft. 6 in. - 24 ft. 4 in. (5.4 - 7.4 m) maximum	24 - 51 in. (61 - 130 cm)	8 - 12 Wheels



Hay Tedders

Improve feed quality and dry-down time with a Hay Tedder. They provide thorough conditioning and even distribution in all types of hay.

Tedding Width	PTO HP	Number of Rotors
16 ft. 5 in. - 27 ft. (5.0 - 8.2 m)	20 - 55 hp (14.9 - 41.0 kW)	4 - 6



Disc Mowers

Get a clean, even cut over rough ground with a rugged Disc Mower. Perfect for mowing through tough, thick crop.

Cutting Width	PTO HP	Hitch
6 ft. 6 in. - 9 ft. (2.0 - 2.7 m)	40 - 50 hp (29.4 - 37.3 kW)	Cat. 1 or 2



Disc Mower Caddy

The Disc Mower Caddy makes mower hook up easier when it's time to mow.

Minimum HP	PTO	Hitch	Disc Mower Compatibility
15 hp (11.2 kW)	540 rpm	Pull-Type	Cat. 2



Sickle Bar Mowers

Sickle Bar Mowers mow up or down hillsides with a blade angle that can be adjusted from -45 degrees to +90 degrees.

Working Width	Engine HP	Hitch
5 ft. 9 in. - 7 ft. 8 in. (1.8 - 2.3 m)	25 - 50 hp (18.6 - 37.3 kW)	Cat. 1 and 2

You, John Deere and Frontier. Let's work together.



Inline Bale Wrapper

Protect silage bales from harsh weather and preserve feed value with Inline Bale Wrappers.

Power	Bale Capacity	Wrapping Capacity
13 hp (9.7 kW)	5 ft. 6 in. (1.7 m) round	120 bales / hr



3-Point Bale Handling

Transport large round bales effortlessly with a 3-Point Bale Handler. Use the hydraulic Bale Unroller to haul and unroll round bales for feeding.

Description	Bale Capacity ¹	Hitch
3-Pt. Bale Spear (single, and dual tine) 3-Pt. Large Square Bale Spear (triple tine) 3-Pt. Large Dual Round Bale Spear (quad tine) 3-Pt. Bale Unroller	2,000 - 4,000 lb. (907.2 - 1814.4 kg)	Cat. 1, 2, or Cat. 3

¹ Bale Capacity, and Hitch all vary depending on the 3-Point Bale Handling implement chosen. Ask your Dealer for specifics.



Bale Spears

Round or square, whatever the job, there is a Frontier Bale Spear up to the task. Choose from a wide range of single- and triple-tine models to move and stack bales quickly and easily.

Bale Handling Capacity ¹	Loader Series / Carrier ¹
1 Large Round Bale, 1 Large Square Bale or 2 Round Bales 2,000 - 2,500 lb. (907.2 - 1,134.0 kg)	300, 400, 500, 600, and 700 / Global or Cat. 2 Global Carrier

¹ Bale Handling Capacity, Loader Series, and Carrier all vary depending on the spear chosen. Ask your Dealer for specifics.



Round-Bale Hugger

Don't lose volume or nutritional value while moving large round bales. Treat regular or silage bales with care with the gentle-grasping Round-Bale Hugger.

Bale Handling Capacity	Loader Series / Carrier
1 Wrapped Bale	600, 700, and 800 / Global Carrier

TipsNotebook.com

A compilation of tips, ideas & collective wisdom about how to get all kinds of jobs done around your place.

Livestock and Equine Equipment



Hydraulic-Push Manure Spreaders

When you need to cover a lot of ground in a hurry, opt for the Hydraulic-Push Manure Spreader. High-capacity spreader boxes and fast unload times reduce the expenditure of time, fuel, and labor.

Capacity	Minimum Tractor Weight	Hitch
425 - 550 bushels	Depending on model chosen: Minimum tractor weight 16,534 or 26,015 lb. (7,499.7 or 11,825 kg)	Pull-Type

Chain-Unloading Manure Spreaders

Spreading manure is both cost-effective and efficient with a Chain-Unloading Manure Spreader. It spreads material evenly to maximize nutrient value.

Capacity	Minimum Tractor Weight	Hitch
25 - 430 bushels	Minimum tractor weight 961 - 15,340 lb. (435.9 - 6,958.1 kg)	Pull-Type

NEW MS11 Series

3-Point Mounted Liquid Sprayers

Frontier's 3-Point Mounted Sprayers are perfect for spraying pastures, fields, road ditches, fence rows, or specialty crops. Sizes to fit virtually all operations.

Tank Size	Application Width ¹	Operating Weight
45 - 300gal. (1.17 - 1.14 m ³)	Boomless, 10 - 30 ft. (3.04 - 9.14 m) With Boom, 25 - 45 ft. (7.62 - 13.7 m)	Boomless, 460 - 1,619 lb. (209 - 734 kg) With Boom, 2,920 - 3,900 lb. (1,324.5 - 1,769 kg)

NEW LS20 Series

¹Weight estimated with water, properly ballasted tractor required for lifting and operation.

You, John Deere and Frontier. Let's work together.



How To Maintain A Gravel Drive Using
A Box Blade With Hydraulic Scarifiers

Send your project idea to Tipldea@JohnDeere.com. The world will be better for it.



Remove Snow Without A Snowblower



How To Handle Large Round Bales



FRONTIER | TIPS NOTEBOOK

Like an expert in your pocket.

At home or in the field, find our ever-growing collection of more than 100 tips, videos, and collective wisdom about how to get all kinds of jobs done around your place. Brought to you by John Deere and Frontier.

We're all in this together.



Replace A Wire Fence End Post And H-Brace



How To Plow And Till A Vegetable Garden

Cutting and Mowing Equipment



Rotary Cutters

If you need a rugged, mid-priced rotary cutter that can handle heavy grass, thick brush, and weeds, a Frontier Rotary Cutter is worth a closer look.

Working Width	PTO HP	Hitch
48 - 84 in. (121.9 - 213.4 cm)	18 - 90 hp (13.4 - 67.1 kW)	Cat. 1, & adaptable to Cat.2 or Cat.2

Grooming Mowers

The Grooming Mower delivers a smooth cut for lawns, sporting fields, and golf courses.

Working Width	PTO HP	Hitch
48 - 110 in. (121.9 - 279.4 cm)	15 - 75 hp (11.2 - 55.6 kW)	Cat. 1 or 2

Flex-Wing Grooming Mowers

Go with the Flex-Wing Grooming Mowers for a quality cut over uneven fields. Features wider working widths to make quick work at sod farms, golf courses, and parks.

Working Width	PTO HP	Hitch
12 - 17 ft. (3.7 - 5.2 m)	25 - 80 hp (18.6 - 59.7 kW)	Pull-Type

TipsNotebook.com

A compilation of tips, ideas & collective wisdom about how to get all kinds of jobs done around your place.

Snow Removal Equipment



3-Point Snowblowers¹

Move snow out of the way so you can get on with your work with a powerful 3-Point Snow Blower. These blowers are the ideal size for large-property and commercial operations, clearing yards, parking lots, driveways, or sidewalks.

Working Width	PTO HP	Hitch
48 - 104 in. (121.9 - 264.2 cm)	16 - 150 hp (11.9 - 111.9 kW)	Cat. 1, 2 or 3

NEW SB11P Series

¹Some models may require an additional kit for an optional Quick-Coupler. Ask your Dealer for details.

Front-Mount Snowblowers¹

Power through deep snowdrifts with Front-Mount Snowblowers. Front mounting provides greater visibility and reduces operator fatigue.

Working Width	PTO HP
64 - 80 in. (162.6 - 203.2 cm)	25 - 75 hp (18.6 - 55.9 kW)

NEW SB12F Series

¹Hydraulic Power Pack required for some models. Ask your Dealer for details.

Snow Pushes

The Snow Push is a fast, simple option for moving snow away from buildings, fences, and hard-to-reach areas.

Working Width	Loader Series
48 - 120 in. (121.9 - 304.8 cm)	100, 300E, 300, 400, or 500 Series Loader

Front Blades

For small snow removal chores, Front Blades are a dependable solution. Curved blade edges roll snow rather than pushing it for smoother, easier moving.

Working Width	Loader Series / Carrier
60 - 120 in. (152.4 - 304.8 cm)	100 - 700 Series Loader / Global Carrier

iMatch™ Quick Hitch



- Provides easy hookup for most Category 1 implements
- Built with tubular, box-welded steel for longer life
- Handles the increased lift capacity of today's high-performance tractors
- Fits all 1- 4 Series John Deere Tractors

Designed to meet the ASABE AD11001 Standard for Category 1 quick hitches.

Material Handling Equipment (Loader Attachments)



Loader Carrier Adapters

Want to upgrade to a John Deere Compact Utility Tractor, but have a collection of skid steer loader attachments you don't want to give up? The Frontier Loader Carrier Adapter is the answer.

Description	Loader Series / Carrier ¹
1500 - 5000 lb. (680.4 - 2,268 kg) Lift Capacity	100, 200, 300E, 300R, 400, 500, 600, or 700 Series Loader / Global Carrier to Skid Steer, Global Carrier, or 500 Quick Attach

¹Loader Series / Carrier selection depends on the Loader Carrier Adapter chosen. Ask your Dealer for specific pairings.

Pallet Forks

Don't let heavy objects weigh down your workday. With Frontier Pallet Forks, you can lift pallets, load lumber, move bulky material, or clear construction sites quickly and efficiently.

Description	Loader Series / Carrier ¹
36 - 49 in. (91.4 - 106.7 cm) Fork Length Fixed tine or floating tine	100, 200, 300, 400, 500, 600, or 700 Series Loader / Global and Category 2 Global

¹Loader Series / Carrier selection depends on the Pallet Fork chosen. Ask your Dealer for specifics.

Mechanical Grapple

The MG20F Mechanical Grapple was designed to meet the needs of those Rural Lifestyle Customers that want a loader grapple, but don't have loader third function capabilities.

Description	Loader Series / Carrier ¹
1200 - 3500 lb. (544.3 - 1588 kg) Lift Capacity	120R, 220R, 300E, 4040R Non self leveling loader, & 500 Loader Series

NEW MG20 Series

¹Loader Series / Carrier selection depends on the Mechanical Grapple chosen. Ask your Dealer for specific pairings.

Pallet Fork Grapples

A great tool for moving lots of materials that are awkward to handle. From piles of brush to firewood to lengths of pipe and more, a Pallet Fork Grapple can help make life simpler and easier.

Description	Attaches To
36 - 39 in. (91.4 - 99.1 cm) Grapple Clamp Length, fixed tine or floating tine	API0, API1, API2, or API2G Pallet Forks



Root Grapples

Get rid of unwanted brush, rocks, logs, and other debris with a Root Grapple. It is the perfect tool for storm cleanup or clearing land of rubble and debris.

Working Width	Loader Series / Carrier
53 - 77 in. (134.6 - 195.6 cm)	100, 200, 300E, 320R, 400, or 500 Series Loader / Global Carrier



Debris Grapples

Grounds maintenance workers and demolition crews can clean up worksites quickly and efficiently with a powerful Debris Grapple. The rugged construction enables operators to clutch heavy or bulky items more easily.

Working Width	Loader Series
60 - 72 in. (152.4 - 182.9 cm)	300, 400, or 500 Series Loader



Rock Buckets

Clear your land of rocks while leaving the soil in place with a Rock Bucket. They sift out soil while picking up heavy rocks or large debris.

Working Width	Loader Series / Carrier
55 - 75 in. (139.7 - 190.5 cm)	300, 400, or 500 Series Loader / Global Carrier



Manure Forks

Move manure or clean up hay with a Frontier Manure Fork.

Working Width	Loader Series / Carrier
50 - 60 in. (127 - 152.4 cm)	100, 200, or 300 Series Loader

You, John Deere and Frontier. Let's work together.



4-In-1 Bucket

Move loose material, clear logs or debris, or grade and smooth driveways with the versatile 4-in-1 Bucket. Move loose material, clear logs or debris, or grade and smooth driveways with the versatile 4-in-1 Bucket.

Working Width	Loader Series
53 in. (134.6 cm)	100, 200, and 300E Series Loader



Loader-Mount Rotary Brooms

Sweep walks, driveways, parking lots, and other paved areas with a Loader-Mount Rotary Broom. These brooms can save valuable time in commercial applications.

Working Width	Loader Series
60 - 84 in. (152.4 - 213.4 cm)	300 or 400 Series Loader



Hydraulic Power Packs

A Frontier Hydraulic Power Pack powers several loader-mount implements to remove snow, dirt, and debris, or take on other tough challenges.

Hydraulic Capacity	PTO HP
16 - 20 GPM / 2,700 - 3,000 psi (60.57 - 75.71 LPM / 18,620 - 20,680 kPa)	25 - 56 hp (18.6 - 41.0 kW)

TipsNotebook.com

A compilation of tips, ideas & collective wisdom about how to get all kinds of jobs done around your place.

Rear Blades

MODEL	DUTY/WORKING WIDTH	PTO HP**	HITCH
RB5048L	Economy / 48 in. (121.9 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
RB5060L	Economy / 60 in. (152.4 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
RB2060L	Economy / 60 in. (152.4 cm)	25 hp (18.6 kW) maximum	Ltd. Cat. 1
RB2060	Standard / 60 in. (152.4 cm)	19 - 45 hp (14.1 - 33.6 kW)	Cat. 1
RB5060	Standard / 60 in. (152.4 cm)	20 - 56 hp (14.9 - 41.8 kW)	Cat. 1
RB2160**	Medium / 60 in. (152.4 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2160H**	Standard Plus / 60 in. (152.4 cm)	50 hp (37.3 kW) maximum	Cat. 1
RB2072	Standard / 72 in. (182.9 cm)	23 - 55 hp (17.1 - 41.0 kW)	Cat. 1
RB5072	Standard / 72 in. (182.9 cm)	20 - 56 hp (14.9 - 41.8 kW)	Cat. 1
RB2172	Medium / 72 in. (182.9 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2172H**	Standard Plus / 72 in. (182.9 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2272**	Medium Plus / 72 in. (182.9 cm)	80 hp (59.6 kW) maximum	Cat. 2
RB2084	Standard / 84 in. (213.4 cm)	27 - 55 hp (20.1 - 41.0 kW)	Cat. 1
RB5084	Standard / 84 in. (213.4 cm)	20 - 56 hp (14.9 - 41.8 kW)	Cat. 1
RB2184**	Medium / 84 in. (213.4 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2184H**	Standard Plus / 84 in. (213.4 cm)	50 hp (37.3 kW) maximum	Cat. 1
RB2284**	Medium Plus / 84 in. (213.4 cm)	80 hp (59.6 kW) maximum	Cat. 2
RB2307* **	Heavy / 84 in. (213.4 cm)	120 hp (89.5 kW) maximum	Cat. 2
RB5096	Standard / 96 in. (243.8 cm)	20 - 56 hp (14.9 - 41.8 kW)	Cat. 1
RB2308* **	Heavy / 96 in. (243.8 cm)	120 hp (89.5 kW) maximum	Cat. 2
RB2196**	Medium / 96 in. (243.8 cm)	65 hp (48.5 kW) maximum	Cat. 1
RB2196H**	Standard Plus / 96 in. (243.8 cm)	50 hp (37.3 kW) maximum	Cat. 1
RB2296**	Medium Plus / 96 in. (243.8 cm)	80 hp (59.7 kW) maximum	Cat. 2
RB2408* **	Heavy Plus / 96 in. (243.8 cm)	160 hp (119.3 kW) maximum	Cat. 2 and 3
RB2309* **	Heavy / 108 in. (274.3 cm)	120 hp (89.5 kW) maximum	Cat. 2
RB2409* **	Heavy Plus / 108 in. (274.3 cm)	160 hp (119.3 kW) maximum	Cat. 2 and 3
RB2310* **	Heavy / 120 in. (304.8 cm)	120 hp (89.5 kW) maximum	Cat. 2
RB2410* **	Heavy Plus / 120 in. (304.8 cm)	160 hp (119.3 kW) maximum	Cat. 2 and 3

*Hydraulic tilt, angle, and offset function available **Reduce the hp requirement by 10 hp if the tractor has MFWD

Box Blades

MODEL	WORKING WIDTH	PTO HP	HITCH
BB2048L	48 in. (121.9 cm)	25 hp (18.6 kW) maximum	Cat. 0 and Ltd. Cat. 1
BB2048	48 in. (121.9 cm)	45 hp (33.5 kW) maximum	Cat. 1
BB5048L	48 in. (121.9 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
BB2060	60 in. (152.4 cm)	55 hp (41 kW) maximum	Cat. 1
BB5060L	60 in. (152.4 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
BB5060	61.5 in. (156.2 cm)	17 - 56 hp (12.8 - 41.8 kW) maximum	Cat. 1
BB2065	66 in. (167.6 cm)	55 hp (41.0 kW) maximum	Cat. 1
BB2072	72 in. (182.9 cm)	55 hp (41.0 kW) maximum	Cat. 1
BB5072	73.5 in. (186.7 cm)	56 hp (41.8 kW) maximum	Cat. 1
BB5084	85.5 in. (217.2 cm)	56 hp (41.8 kW) maximum	Cat. 1
BB5096	97.5 in. (247.7 cm)	56 hp (41.8 kW) maximum	Cat. 1

Land Planes

MODEL	WORKING WIDTH	SCARIFIERS	PTO HP	HITCH
LP2054L	54 in. (137.2 cm)	4	18-30 hp (13.4 - 22.4 kW)	Clevis with Pin; Ltd. Cat 1
LP2160	60 in. (152.4 cm)	4	25-50 hp (18.6 - 37.3 kW)	Clevis with Pin; Cat 1
LP2172	72 in. (182.9 cm)	5	25-50 hp (18.6 - 37.3 kW)	Clevis with Pin; Cat 1
LP2184	84 in. (213.4 cm)	6	40-90 hp (29.8 - 67.1 kW)	Clevis with Pin; Cat 1 and 2
LP2196	96 in. (243.8 cm)	7	40-90 hp (29.8 - 67.1 kW)	Clevis with Pin; Cat 1 and 2

Landscape Rakes

MODEL	DUTY/WORKING WIDTH	PTO HP	HITCH
LR5048L	Economy / 48 in. (121.9 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
LR2060L	Economy / 60 in. (152.4 cm)	25 hp (18.1 kW) maximum	Ltd. Cat. 1
LR5060L	Standard / 60 in. (152.4 cm)	18 hp (13.4 kW) maximum	Ltd. Cat. 1
LR5060	Standard / 72 in. (182.9 cm)	12 - 40 hp (8.9 - 29.8 kW)	Cat. 1
LR2072	Standard / 72 in. (182.9 cm)	19 - 40 hp (14.2 - 29.8 kW)	Cat. 1

MODEL	DUTY/WORKING WIDTH	PTO HP	HITCH
LR5072	Standard / 72 in. (182.9 cm)	20 - 38 hp (14.9 - 28.3 kW)	Cat. 1
LR2172	Medium / 72 in. (182.9 cm)	23 - 55 hp (17.2 - 41.0 kW)	Cat. 1
LR2084	Standard / 84 in. (213.4 cm)	19 - 40 hp (14.2 - 29.8 kW)	Cat. 1
LR5084	Standard / 84 in. (213.4 cm)	20 - 50 hp (14.9 - 37.3 kW)	Cat. 1
LR2184	Medium / 84 in. (213.4 cm)	23 - 55 hp (17.2 - 41.0 kW)	Cat. 1
LR5096	Standard / 96 in. (243.8 cm)	20 - 50 hp (14.9 - 37.3 kW)	Cat. 1
LR2196	Medium / 96 in. (243.8 cm)	27 - 55 hp (20.1 - 41.0 kW)	Cat. 1

Wood Chippers

MODEL	FEED OPENING	LIMB	PTO HP	HITCH
WC1103	3 x 5.5 in. (7.6 x 14.0 cm)	3 in. (7.6 cm)	18 - 40 hp (13.4 - 29.8 kW)	Cat. 1
WC1105	5.5 x 8 in. (14.0 x 20.3 cm)	5 in. (12.7 cm)	25 - 85 hp (18.6 - 63.4 kW)	Cat. 1 and 2
WC1205	5.5 x 8 in. (14.0 x 20.3 cm)	5 in. (12.7 cm)	35 - 95 hp (26.1 - 70.8 kW)	Cat. 1 and 2

Soil Pulverizers

MODEL	DUTY/WORKING WIDTH	PTO HP	SCARIFIER TEETH	HITCH
SP2048B	Standard / 48 in. (121.9 cm)	30 - 45 hp (22.3 - 33.6 kW)	Bar Type	Cat. 1
SP2060B	Standard / 60 in. (152.4 cm)	30 - 45 hp (22.4 - 33.6 kW)	Bar Type	Cat. 1
SP2072B	Standard / 72 in. (182.9 cm)	30 - 45 hp (22.4 - 33.6 kW)	Bar Type	Cat. 1
SP2272B	Heavy / 72 in. (182.9 cm)	30 - 70 hp (22.3 - 52.2 kW)	Bar Type	Cat. 1
SP2284B	Heavy / 84 in. (213.4 cm)	30 - 70 hp (22.3 - 52.2 kW)	Bar Type	Cat. 1

Post Hole Diggers

MODEL	AUGER LENGTH	PTO HP	HITCH
PHD100	36 in. (91.4 cm)	15 - 25 hp (10.8 - 18.6 kW)	Cat. 1
PHD200	48 in. (121.9 cm)	18 - 40 hp (13.4 - 29.8 kW)	Cat. 1
PHD300	48 in. (121.9 cm)	18 - 50 hp (13.4 - 37.3 kW)	Cat. 1 and 2
PHD400	48 in. (121.9 cm)	40 - 90 hp (29.8 - 67.1 kW)	Cat. 1 and 2

MODEL	AUGER LENGTH	PTO HP	HITCH
PHD125	36 in. (91.4 cm)	15 - 25 hp (10.8 - 18.6 kW)	Cat. 1 and Ltd. Cat. 1
PHD235	48 in. (121.9 cm)	20 - 35 hp (14.9 - 26 kW)	Cat. 1
PHD395	48 in. (121.9 cm)	35 - 95 hp (26 - 70.8 kW)	Cat. 1 and 2

3-Point Trencher

MODEL	AUGER LENGTH	PTO HP	HITCH
DT1136	36 in. (91.4 cm)	15 - 30 hp (11.2 - 22.4 kW) Hydrostatic Transmission Only	Cat. 1

Core Aerators

MODEL	DUTY/WORKING WIDTH	PTO HP	HITCH
CA2048E	Economy / 48 in. (121.9 cm)	20 - 50 hp (14.9 - 37.3 kW)	Cat. 1
CA2060E	Economy / 60 in. (152.4 cm)	20 - 50 hp (14.9 - 37.3 kW)	Cat. 1
CA2060	Economy / 60 in. (152.4 cm)	25 - 70 hp (18.6 - 52.2 kW)	Cat. 1 and 2
CA2072E	Economy / 72 in. (182.9 cm)	20 - 50 hp (14.9 - 37.3 kW)	Cat. 1
CA2072	Standard / 72 in. (182.9 cm)	25 - 70 hp (18.6 - 52.2 kW)	Cat. 1 and 2

3-Point Debris Blower

MODEL	PTO HP	HITCH
BL1130	25 hp (18.6 kW) minimum	Cat. 1 and 2

Material Collection System

MODEL	HOPPER CAPACITY	MOWER COMPATIBILITY	TRACTOR COMPATIBILITY
MC2014	14 Bushel (393.3 l)	54D, 60D, 72D	1023E, 1025R, 2025R, 2032R, 2038R, 3033R, 3039R, 3046R
MC2120	20 Bushel (704.8 l)	54D, 60D, 72D	1023E, 1025R, 2025R, 2032R, 2038R, 3033R, 3039R, 3046R

Power Rakes

MODEL	WORKING WIDTH	PTO HP	HITCH
PR1148	Hydraulic / 48 in. (121.9 cm)	15 - 22 hp (11.2 - 16.4 kW)	Cat. 1
PR1160	Hydraulic / 60 in. (152.4 cm)	18 - 35 hp (13.4 - 26.1 kW)	Cat. 1
PR1172	Hydraulic / 72 in. (182.9 cm)	30 - 40 hp (22.4 - 29.8 kW)	Cat. 1
PR1184	Hydraulic / 84 in. (213.4 cm)	42 - 80 hp (31.3 - 59.6 kW)	Cat. 1 and 2

Tandem Disks

MODEL	WORKING WIDTH	PTO HP OR DRAWBAR	WEIGHT / DISK	DISK QUANTITY
TM5118	18 ft. (5.5 m) folding	160-180 HP (119.3 – 134.2 kW)	369 lb. (167.4 kg)	46
TM5120	19 ft. 6 in. (6.1 m) folding	170-200 HP (127 – 149.1 kW)	345 lb. (157 kg)	50
TM5121	21 ft. (6.4 m) folding	190-210 HP (142 – 157 kW)	322 lb. (146.1 kg)	54
TM5124	23 ft. 6 in. (7.3 m) folding	220+ HP (164+ kW)	320 lb. (145.1 kg)	58
TM5129	29 ft. (8.8 m) folding	260+ HP (194+ kW)	314 lb. (142.4 kg)	74
TM5132	32 ft. (9.8 m) folding	280+ HP (209+ kW)	309 lb. (140.2 kg)	82

Tandem Disks Harrows

MODEL	WORKING WIDTH	ENGINE HP	WEIGHT	DISK QTY.	HITCH
TM1048	48 in (121.9 cm)	28 hp (20.9 kW)	388 lb (176 kg)	12	Limited Cat. 1
TM1062L	62 in (157.5 cm)	28 hp (20.9 kW)	445 lb (201.8 kg)	16	Cat. 1
TM1164	62 in (157.5 cm)	45 hp (33.6 kW)	660 lb (299.4 kg)	16	Cat. 1
TM1173	73 in (185.4 cm)	45 hp (33.6 kW)	705 lb (319.8 kg)	16	Cat. 1
TM1179	79 in (200.7 cm)	45 hp (33.6 kW)	735 lb (333.4 kg)	20	Cat. 1
TM1275	75 in (190.5 cm)	40-75 hp (29.8 – 55.9 kW)	890 lb (403.7 kg)	16	Cat. 1
TM1292	92 in (233.7 cm)	40-75 hp (29.8 – 55.9 kW)	968 lb (439.1 kg)	20	Cat. 1
TM1396	96 in (243.8 cm)	45-100 hp (33.6 – 74.6 kW)	1346 lb (610.5 kg)	20	Cat. 1 and 2

You, John Deere and Frontier. Let's work together.

One-Row Cultivator

MODEL	ROW WIDTH	PTO HP	HITCH
PC1001	30 - 60 in. (76.2 - 152.4 cm)	18 - 45 hp (13.4 - 33.6 kW)	3-Pt. / Cat. 1

Rotary Tillers

MODEL	DUTY / WIDTH	PTO HP	HITCH
RT1265	Medium / 65 in. (165.1 cm)	30 - 60 hp (22.4 - 44.7 kW)	3-Pt. / Cat. 1 and 2
RT1273	Medium / 73 in. (185.4 cm)	50 - 80 hp (37.3 - 59.7 kW)	3-Pt. / Cat. 2
RT2283	Medium / 83 in. (210.8 cm)	60 - 100 hp (44.7 - 74.6 kW)	3-Pt. / Cat. 2
RT2293	Medium / 93 in. (236.2 cm)	70 - 100 hp (52.2 - 74.6 kW)	3-Pt. / Cat. 2
RT2383	Heavy Duty / 83 in. (210.8 cm)	80 - 130 hp (59.7 - 96.9 kW)	3-Pt. / Cat. 2
RT2308	Heavy Duty / 102 in. (259.1 cm)	80 - 130 hp (59.7 - 96.9 kW)	3-Pt. / Cat. 2
RT2310	Heavy Duty / 121 in. (307.3 cm)	100 - 130 hp (74.6 - 96.9 kW)	3-Pt. / Cat. 2
RT3042	Standard/42 inch (106.7 cm)	15-35 hp (11.2-26.1 kW)	Ltd. Cat. 1
RT3042R	Standard / 72 in. (182.9 cm)	15-35 hp (11.2-26.1 kW)	Ltd. Cat. 1
RT3049	Standard/49 inch (124.5 cm)	15-35 hp (11.2-26.1 kW)	Ltd. Cat. 1
RT3049R	Standard/49 inch (124.5 cm)	15-35 hp (11.2-26.1 kW)	Ltd. Cat. 1
RT3062	Standard/62 inch (157.5 cm)	19-60 hp (14.2-44.7 kW)	Cat. 1
RT3062R	Standard/62 inch (157.5 cm)	19-60 hp (14.2-44.7 kW)	Cat. 1
RT3073	Standard/73 inch (185.4 cm)	30-60 hp (22.4-44.7 kW)	Cat. 1 and 2
RT3073R	Standard/73 inch (185.4 cm)	30-60 hp (22.4-44.7 kW)	Cat. 1 and 2
RT3081	Standard/81 inch (205.7 cm)	40-60 hp (29.8-44.7 kW)	Cat. 1 and 2
RT3081R	Standard/81 inch (205.7 cm)	40-60 hp (29.8-44.7 kW)	Cat. 1 and 2

Plows

MODEL	MOLDBOARD WIDTH	PTO HP	HITCH
PB1001	One - Bottom / 14 in. (35.6 cm)	25 - 50 hp (13.4 - 37.3 kW)	3-Pt. / Cat. 1
PB1002	Two - Bottom / 40 in. (101.6 cm)	25 - 50 hp (13.4 - 37.3 kW)	3-Pt. / Cat. 1

Field Cultivator

MODEL	WORKING WIDTH	PTO HP	HITCH
PC1072	72 in. (182.9 cm)	18 - 45 hp (13.4 - 33.6 kW)	3-Pt. / Cat. 1

Subsoiler

MODEL	WORKING DEPTH	PTO HP	HITCH
PS1001	Up to 24 in. (61.0 cm)	18 - 45 hp (13.4 - 33.6 kW)	3-Pt. / Cat. 1

Middle Buster

MODEL	WORKING DEPTH	PTO HP	HITCH
PM1001	Up to 12 in. (30.5 cm)	18 - 45 hp (13.4 - 33.6 kW)	3-Pt. / Cat. 1

Overseeders

MODEL	DRIVE	WORKING WIDTH	PTO HP	HITCH
GS1048L	Ground Driven	48 in. (1.22 m)	Minimum 15 hp (11.2 kW)	Ltd. Cat. 1
GS1060L	Ground Driven	60 in. (1.52 m)	Minimum 45 hp (22.3 kW)	Ltd. Cat. 1
GS1148	Ground Driven	48 in. (1.22 m)	Minimum 30 hp (22.3 k)	Cat. 1 and Cat. 2
GS1160	Ground Driven	60 in. (1.52 m)	Minimum 35 hp (26.1 kW)	Cat. 1 and Cat. 2
GS1172	Ground Driven	72 in. (1.83 m)	Minimum 50 hp (37.3 kW)	Cat. 1 and Cat. 2
GS1184	Ground Driven	84 in. (2.13 m)	Minimum 55 hp (41 kW)	Cat. 1 and Cat. 2
TR2058	PTO Driven	58 in. (147.3 cm)	25 - 45 hp (18.6 - 33.6 kW)	Cat. 1

Broadcast Spreaders

MODEL	WORKING WIDTH	PTO HP	HITCH
SS1022B	20 ft. (6.1 m) swath	16 - 30 hp (11.9 - 22.4 kW)	Pull-Type

MODEL	WORKING DEPTH	PTO HP	HITCH
SS1023B	23 ft. (7.0 m) swath	16 - 30 hp (11.9 - 22.4 kW)	Cat. 0 and 1
SS1035B	20 ft. (6.1 m) swath	16 - 45 hp (11.9 - 33.6 kW)	Pull-Type
SS1036B	23 ft. (7.0 m) swath	16 - 45 hp (11.9 - 33.6 kW)	Cat. 1
SS1067B	46 ft. (14.0 m) swath	16 - 55 hp (11.9 - 41.0 kW)	Cat. 1
SS2036B	23 ft. (7.0 m) swath	16 - 45 hp (11.9 - 33.6 kW)	Cat. 1
SS2067B	46 ft. (14.0 m) swath	16 - 55 hp (11.9 - 41.0 kW)	Cat. 1
SS3067B	49 ft. (14.9 m) swath	20 - 60 hp (14.9 - 44.7 kW)	Cat. 1

Pendular Spreaders

MODEL	WORKING WIDTH	PTO HP	HITCH
SS1079P	47 ft. (14.3 m) swath	20 - 60 hp (14.9 - 44.7 kW)	Cat. 1
SS1116P	47 ft. (14.3 m) swath	20 - 60 hp (14.9 - 44.7 kW)	Cat. 1 and 2
SS1180P	47 ft. (14.3 m) swath	20 - 60 hp (14.9 - 44.7 kW)	Cat. 1 and 2
SS1220P	47 ft. (14.3 m) swath	20 - 60 hp (14.9 - 44.7 kW)	Cat. 1 and 2

Conservation Seeders

MODEL	WORKING WIDTH	PTO HP	HITCH
CS1360	5 ft. (1.5 m)	30 hp (22.4 kW) minimum	Cat. 1 and 2
CS1384	7 ft. (2.1 m)	50 hp (37.3 kW) minimum	Cat. 1 and 2

Heavy-Duty Wheel Rake

MODEL	RAKING WIDTH	WINDROW WIDTH	# OF WHEELS
WR5417	29 ft. (8.8 m) maximum	72 in. (182.9 cm) maximum	17 Wheels

High-Capacity Wheel Rakes

MODEL	RAKING WIDTH	WINDROW WIDTH	# OF WHEELS
WR1212	24 ft. (7.3 m) maximum	38 - 58 in. (96.5 - 147.3 cm)	12 Wheels
WR1214	28 ft. (8.5 m) maximum	38 - 58 in. (96.5 - 147.3 cm)	14 Wheels
WR1216	32 ft. (9.8 m) maximum	38 - 58 in. (96.5 - 147.3 cm)	16 Wheels

High-Capacity Carted Wheel Rakes

MODEL	RAKING WIDTH	WINDROW WIDTH	# OF WHEELS
WR3208	16 ft. 6 in. - 17 ft. 8 in. (5 - 5.7 m)	4 ft. 5 in. 6 ft. 10 in. (1.3 - 2.1 m)	8 Wheels
WR3210	18 ft. 5 in. - 21 ft. (5.6 - 6.4 m)	3 ft. 3 in. - 7 ft. 3 in. (1 - 2.2 m)	10 Wheels
WR3212	21 ft. 24 ft. 4 in (6.4 - 7.4 m)	2 ft. 10 in. - 7 ft. 3 in. (.9 - 2.2 m)	12 Wheels

Carted Wheel Rakes

MODEL	RAKING WIDTH	WINDROW WIDTH	# OF WHEELS
WR0008	17 Ft. 8 In. (5.4m)	24 to 51 In. (610 to 1,295 mm)	8 Wheels
WR0010	21 Ft. Maximum (6.4 m)	4 to 51 In. (610 to 1,295 mm)	10 Wheels
WR0012	24 Ft. 4 In. Maximum (7.4 m)	24 to 51 In. (610 to 1,295 mm)	12 Wheels

Hay Tedders

MODEL	TEDDING WIDTH	PTO HP	# OF ROTORS
TD1316	16 ft. 5 in. (5.0 m)	20 hp (14.9 kW)	4
TD3418	18 ft. 2 in. (5.5 m)	30 hp (22.4 kW)	4
TD3427	27 ft. (8.2 m)	55 hp (41.0 kW)	6

Disc Mowers

MODEL	CUTTING WIDTH	PTO HP	HITCH
DM5050	6 ft. 6 in. (2.0 m)	40 hp (29.4 kW)	Cat. 1 or 2
DM5060	7 ft. 9 in. (2.4 m)	45 hp (33.1 kW)	Cat. 1 or 2
DM5070	9 ft. (2.7 m)	50 hp (40.5 kW)	Cat. 2

Sickle Bar Mowers

MODEL	WORKING WIDTH	ENGINE HP	HITCH
SB3106	5 ft. 9 in. (1.75 m)	25-50hp	Cat 1, Cat 2, Imatch Compatible
SB3107	6 ft. 9 in. (2.05 m)	25-50hp	Cat 1, Cat 2, Imatch Compatible
SB3108	7 Ft. 8 In. (2.35 m)	25-50hp	Cat 1, Cat 2, Imatch Compatible

Inline Bale Wrapper

MODEL	POWER	BALE CAPACITY	WRAPPING CAPACITY
LW1166	13 hp (9.7 kW)	5 ft. 6 in. (1.7 m) round	120 bales / hr

3-Point Bale Unroller

MODEL	DESCRIPTION	BALE CAPACITY	HITCH
BU1060	3 Pt. Bale Unroller	2000 lb. (907.2 kg)	Cat. 1 and 2

You, John Deere and Frontier. Let's work together.

3-Point Bale Spears

MODEL	DESCRIPTION	BALE CAPACITY	HITCH
HS2001	3 Pt. Bale Spear (single tine)	2200 lb. (997.9 kg)	Cat. 1 and 2
HS2002	3 Pt. Bale Spear (dual tine)	3000 lb. (1360.8 kg)	Cat. 2 and 3
HS2003	3 Pt. Large Square Bale Spear (triple tine)	3000 lb. (1360.8 kg)	Cat. 2 and 3
HS2004	3 Pt. Large Dual Round Bale Spear (quad tine)	4000 lb. (1814.4 kg)	Cat. 2 and 3

Round Bale Hugger

MODEL	BALE CAPACITY	LOADER SERIES / CARRIER
AH11	1 Wrapped Bale	600 and 700 Series Loader / Global Carrier

Hydraulic-Push Manure Spreaders

MODEL	CAPACITY	MINIMUM TRACTOR WEIGHT	HITCH
MS1442	425 bushels	16,534 lb. (7,499.7 kg)	Pull-Type
MS1455	550 bushels	21,620 lb. (9,806.7 kg)	Pull-Type

Chain-Unloading Manure Spreaders

MODEL	CAPACITY	MINIMUM TRACTOR WEIGHT	HITCH
MS1102G	25 bushels	961 lb. (435.9 kg)	Pull-Type
MS1105G	50 bushels	2,176 lb. (987.0 kg)	Pull-Type
MS1108G	80 bushels	2,851 lb. (1,293.2 kg)	Pull-Type
MS1108	80 bushels	3,282 lb. (1,488.7 kg)	Pull-Type
MS1112	125 bushels	4,547 lb. (2,062.5 kg)	Pull-Type
MS1223	175 bushels	5,670 lb. (2,571.9 kg)	Pull-Type
MS1117	235 bushels	7,742 lb. (3,511.7 kg)	Pull-Type
MS1223	270 bushels	9,068 lb. (4,113.2 kg)	Pull-Type
MS1227	310 bushels	10,532 lb. (4,777.2 kg)	Pull-Type

MODEL	CAPACITY	MINIMUM TRACTOR WEIGHT	HITCH
MS1237	370 bushels	13,164 lb. (5,971.1 kg)	Pull-Type
MS1243	430 bushels	15,340 lb. (6,958.1 kg)	Pull-Type

3-pt Mounted Sprayers

MODEL	WORKING WIDTH	TANK CAPACITY	OPERATING WEIGHT*	HITCH
LS1125	25 ft. (7.62 m)	Tank One - 250 gal. (946 L) Tank Two - 300 gal. (1136 L)	2,920 lb (1,324.5 kg) 3,350 lb (1,519.5 kg)	Cat. 2 and 3 3-pt hitch with quick-hitch
LS1130	30 ft (9.14 m)	Tank One - 250 gal. (946 L) Tank Two - 300 gal. (1136 L)	2,950 lb (1,338.1 kg) 3,375 lb (1,530.9 kg)	Cat. 2 and 3 3-pt hitch with quick-hitch
LS1130BL	Up to 30 ft (up to 9.14 m)	Tank One - 250 gal. (946 L) Tank Two - 300 gal. (1136 L)	2,730 lb (1,238.3 kg) 3,155 lb (1,431.1 kg)	Cat. 2 and 3 3-pt hitch with quick-hitch
LS1140	40 ft (12.19m)	Tank One - 250 gal. (946 L) Tank Two - 300 gal. (1136 L)	2,970 lb (1,347.2 kg) 3,400 lb (1,542.2 kg)	Cat. 2 and 3 3-pt hitch with quick-hitch
LS1145	45 ft (13.72 m)	Tank One - 250 gal. (946 L) Tank Two - 300 gal. (1136 L)	3,470 lb (1,573. kg) 3,900 lb (1,769. kg)	Cat. 2 and 3 3-pt hitch with quick-hitch
LS2004	10 ft (3 m) 12.5 ft (3.8 m) 24 ft (7.3 m)	45 gal. (170 L)	460 lb (209 kg)	Limited Cat 1. and Cat. 1 with quick-hitch
LS2006	12.5 ft (3.8 m) 18 ft (5.5 m) 24 ft (7.3 m)	60 gal. (227 L)	610 lb (277 kg)	Cat. 1 with quick-hitch
LS2011	18 ft (5.5 m) 24 ft (7.3 m) 30 ft (9.1 m)	110 gal. (416 L)	1,216 lb (551 kg)	Cat. 1 or Cat. 2 (with optional kit) with quick-hitch
LS2015	24 ft (7.3 m) 30 ft (9.1 m)	150 gal. (568 L)	1,619 lb. (734 kg)	Cat. 2 with quick-hitch

*Weight estimated with water. Properly ballasted tractor required for lifting and operation.

Rotary Cutters

MODEL	WORKING WIDTH	PTO HP	HITCH
RC2048	48 in. (121.9 cm)	18 – 45 hp (13.4 – 33.6 kW)	Cat. 1 and Cat.2
RC2060	60 in. (152.4 cm)	19 - 65 hp (14.2 - 48.5 kW)	Cat. 1 and Cat.2
RC2072	72 in. (182.9 cm)	25 – 65 hp (18.6 – 48.5 kW)	Cat. 1 and Cat.2
RC2084	84 in. (213.4 cm)	45 – 90 hp (33.6 – 67.1 kW)	Cat. 2
RC4048	48 in. (121.9 cm)	15 – 40 hp (11.2 – 29.8 kW)	Cat. 1
RC4060	60 in. (152.4 cm)	20 – 55 hp (14.9 – 41 kW)	Cat. 1
RC4072	72 in. (182.9 cm)	25 – 55 hp (18.6 – 41 kW)	Cat. 1

Grooming Mowers

MODEL	WORKING WIDTH	PTO HP	HITCH
GM1048E	48 in. (121.9 cm)	16 – 30 hp (11.9 – 22.4 kW)	Cat. 1
GM1060E	60 in. (152.4 cm)	18 – 30 hp (13.4 – 22.4 kW)	Cat. 1
GM1072E	72 in. (182.9 cm)	22 – 30 hp (16.4 – 22.4 kW)	Cat. 1
GM1190	90 in. (228.6 cm)	25 – 50 hp (18.6 – 37.3 kW)	Cat. 1
GM2060R	60 in. (152.4 cm)	20 – 50 hp (14.9 – 37.3 kW)	Cat. 1
GM2072R	72 in. (182.9 cm)	20 – 50 hp (14.9 – 37.3 kW)	Cat. 1
GM2084R	84 in. (213.4 cm)	20 – 50 hp (14.9 – 37.3 kW)	Cat. 1
GM2109R	110 in. (279.4 cm)	30 – 70 hp (22.4 – 52.2 kW)	Cat. 1
GM2190R	90 in. (228.6 cm)	30 – 70 hp (22.4 – 52.2 kW)	Cat. 1
GM4060E	60 in. (152.4 cm)	15 – 50 hp (11.2 – 37.3 kW)	Cat. 1 and Ltd. Cat. 1
GM4060	60 in. (152.4 cm)	15 – 40 hp (11.2 – 29.8 kW)	Cat. 1
GM4072E	72 in. (182.9 cm)	20 – 50 hp (14.9 – 37.3 kW)	Cat. 1
GM4072	72 in. (182.9 cm)	20 – 40 hp (14.9 – 29.8 kW)	Cat. 1
GM4084	84 in. (213.4 cm)	25 – 40 hp (18.6 – 29.8 kW)	Cat. 1

Flex-Wing Grooming Mowers

MODEL	WORKING WIDTH	PTO HP	HITCH
FM1012	12 ft. (3.7 m)	30 – 80 hp (22.4 – 59.7 kW)	Pull-Type
FM1015	15 ft. (4.6 m)	35 – 80 hp (26.1 – 59.7 kW)	Pull-Type
FM1017	17 ft. (5.2 m)	40 – 80 hp (29.8 – 59.7 kW)	Pull-Type
FM4012	12 ft. (3.7 m)	25 – 60 hp (18.6 – 44.7 kW)	Pull-Type
FM4112	12 ft. (3.7 m)	30 hp (22.4 kW)	Clevis Hitch
FM4115	15 ft. (4.6 m)	35 hp (26.1 kW)	Clevis Hitch
FM4117	17 ft. (5.2 m)	40 hp (29.8 kW)	Clevis Hitch

TipsNotebook.com

A compilation of tips, ideas & collective wisdom about how to get all kinds of jobs done around your place.

3-Point Snowblowers

MODEL	WORKING WIDTH	PTO HP	HITCH
SBI148	48 in. (121.9 cm)	16 - 35 hp (11.9 - 26.1 kW)	Cat. 1
SBI154	54 in. (137.2 cm)	16 - 35 hp (11.9 - 26.1 kW)	Cat. 1
SBI164	64 in. (162.6 cm)	20 - 50 hp (14.9 - 37.3 kW)	Cat. 1
SBI174	74 in. (188.0 cm)	30 - 50 hp (22.4 - 37.3 kW)	Cat. 1
SBI184	84 in. (213.4 cm)	35 - 90 hp (26.1 - 67.1 kW)	Cat. 1 and Cat. 2
SBI194	94 in. (238.8 cm)	35 - 90 hp (26.1 - 67.1 kW)	Cat. 2
SBI274	74 in. (188.0 cm)	30 - 80 hp (22.4 - 59.7 kW)	Cat. 1 and Cat. 2
SBI280	80 in. (203.2 cm)	30 - 80 hp (22.4 - 59.7 kW)	Cat. 1 and Cat. 2
SBI308R	98 in. (248.9 cm)	100 - 150 hp (74.6 - 111.9 kW)	Cat. 2 and Cat. 3
SBI309R	104 in. (264.2 cm)	100 - 150 hp (74.6 - 111.9 kW)	Cat. 2 and Cat. 3
SBI388	88 in. (223.5 cm)	55 - 95 hp (41.0 - 70.8 kW)	Cat. 2
SBI388R	88 in. (223.5 cm)	55 - 95 hp (41.0 - 70.8 kW)	Cat. 2
SBI392R	92 in. (233.7 cm)	75 - 125 hp (55.9 - 93.2 kW)	Cat. 2

Pull Type Snowblowers

MODEL	WORKING WIDTH	PTO HP	HITCH
SBI164P	64 in. (162.6 cm)	20 - 50 hp (15 - 37.3 kW)	3-Point Cat. 1
SBI174P	74 in. (188 cm)	20 - 65 hp (15 - 48.5 kW)	3-Point Cat. 1

Front-Mount Snowblowers

MODEL	WORKING WIDTH	PTO HP
SB2164	64 in. (163 cm)	25 - 34 hp (18.6 - 25.4 kW)
SB2176	76 in. (193 cm)	35 - 46 hp (26.1 - 34.3 kW)
SBI280F	80 in. (203.2 cm)	40-75 hp (29.8 - 55.9 kW)

Snow Pushes

MODEL	WORKING WIDTH	LOADER SERIES
AS10F	64 in. (163 cm)	100 and 200 Series
AS10H-6	73.75 in. (187.3 cm)	300 and 400 Series
AS10H-7	85.75 in. (217.8 cm)	300 and 400 Series
AS10H-8	97.75 in. (248.3 cm)	300 and 400 Series
AS11E-8	98 in. (248.9 cm)	300, 400, and 500 Series
AS11E-9	110 in. (279.4 cm)	300, 400, and 500 Series
AS11E-10	119 in. (303.5 cm)	300, 400, and 500 Series

Front Blades

MODEL	WORKING WIDTH	LOADER SERIES / CARRIER
AF10F	60 in. (152.4 cm)	100 and 200 Series
AF11D	84 in. (213.4 cm)	300, 400, 500, 600, and 700 Series / Global Carrier
AF11E	72 in. (182.9 cm)	300, 400, and 500 Series
AF11G	96 in. (243.8 cm)	600 and 700 Series / Global Carrier
AF12D	108 in. (274.3 cm)	600 and 700 Series / Global Carrier
AF12G	120 in. (304.8 cm)	600 and 700 Series / Global Carrier

Loader Carrier Adapters

MODEL	DESCRIPTION	LOADER SERIES / CARRIER
SA20F	1500 lbs. (680.4 kg) Lift Capacity	100, 200, 300E Series to Skid Steer
SA21E	4,000 lb (1,814.4 kg) Lift Capacity	300R, 400 and 500 Series to Skid Steer
SA21G	4,000 lb (1,814.4 kg) Lift Capacity	Global Carrier to Skid Steer
SA22D	5,000 lb (2,268 kg) Lift Capacity	600 and 700 Series to Skid Steer
DA21G	4,000 lb (1,814.4 kg) Lift Capacity	Global Carrier to 500 Quick Attach
GA21E	4,000 lb (1,814.4 kg) Lift Capacity	400 and 500 Series to Global Carrier
GA22D	5,000 lb (2,268 kg) Lift Capacity	600 Series to Global Carrier

Pallet Forks

MODEL	DESCRIPTION	LOADER SERIES / CARRIER
AP10F	36 in. (91.44 cm) Fixed Tine Pallet Fork	100 Series
AP10F	42 in. (106.7 cm) Fixed Tine Pallet Fork	100 Series
AP11F	36 in. (91.44 cm) Fixed Tine Pallet Fork	200 to 500 Series
AP11F	42 in. (106.7 cm) Fixed Tine Pallet Fork	200 to 500 Series
AP11G	49 in (124.5 cm) Fixed Tine Pallet Fork	Global Carrier
AP12D	Fixed	600 and 700 Series
AP12F	Fixed	200 to 500 Series
AP12G	Fixed	Global Carrier
AP12K	Fixed	Global Carrier – Category 2
AP13D	Floating	600 and 700 Series
AP13G	Floating	Global Carrier

Mechanical Grapple

MODEL	WIDTH	LIFT CAPACITY	LOADER COMPATIBILITY
MG20F	54 in. (137.2 cm)	1200 lbs. (544.3 kg)	120R, 220R, 300E

Pallet Fork Grapples

MODEL	PALLET FORK COMPATIBILITY
PG11	AP10 Series and AP11 Series
PG12	AP12 Series

You, John Deere and Frontier. Let's work together.

Root Grapples

MODEL	WORKING WIDTH	LOADER SERIES / CARRIER
AV20F	53 in. (134.6 cm)	100 to 300 Series
AV20H	60 in. (152.4 cm)	300 and 400 Series
AV20E	62 in. (157.5 cm)	100, 400, and 500 Series
AV20G	77 in. (195.6 cm)	Global Carrier

Debris Grapples

MODEL	WORKING WIDTH	LOADER SERIES / CARRIER
AD11H	60 in. (152.4 cm)	300 and 400 Series
AD11E	72 in. (182.9 cm)	300, 400, and 500 Series
AD12G	76 in. (193.0 cm)	600 and 700 Series / Global Carrier

Rock Buckets

MODEL	WORKING WIDTH	LOADER SERIES / CARRIER
AR10H	55 in. (138.7 cm)	300 and 400 Series
AR10E	66 in. (167.6 cm)	300, 400, and 500 Series
AR10E	75 in. (190.5 cm)	300, 400, and 500 Series
AR10G	75 in. (190.5 cm)	Global Carrier

Manure Forks

MODEL	DESCRIPTION	LOADER SERIES / CARRIER
AM20F	50 in. (127 cm) Manure Fork	100 Series
AM20F	60 in. (152.4 cm) Manure Fork	100, 200, 300 Series

4-In-1 Bucket

MODEL	WORKING WIDTH	LOADER SERIES / CARRIER
AY11F	53 in. (134.6 cm)	100 to 300 Series

Loader-Mount Rotary Brooms

MODEL	WORKING WIDTH	LOADER SERIES / CARRIER
SW2160	60 in. (152.4 cm)	300 Series
SW2172	72 in. (182.9 cm)	300 or 400 Series
SW2184	84 in. (213.4 cm)	400 Series

Hydraulic Power Packs

MODEL	HYDRAULIC CAPACITY	PTO HP
HP2025	16 GPM / 2,700 psi (60.57 LPM / 18,620 kPa)	25 - 35 hp (18.6 - 26.1 kW)
HP2134	20 GPM / 3,000 psi (75.71 LPM / 20,680 kPa)	35 - 56 hp (26.1 - 41.8 kW)

The logo for Frontier, featuring a stylized white 'F' inside a square frame, followed by the word 'FRONTIER' in a bold, white, sans-serif font.

FRONTIER

This literature has been compiled for worldwide circulation. Some images are representational only. While general information, pictures and descriptions are provided, some illustrations and text may include finance, credit, insurance, and product options/accessories available at an additional cost that may not be available in all regions. CONTACT YOUR LOCAL JOHN DEERE DEALER FOR DETAILS. The iMatch Quick-Hitch does not work with all tractor series or with all implements. See your John Deere dealer to determine which tractors and implements are compatible with the iMatch. The engine horsepower and torque information for non-Deere engines are provided by the engine manufacturer to be used for comparison purposes only. Actual operating horsepower and torque will be less. Refer to the engine manufacturer's web site for additional information. Frontier Equipment reserves the right to change specifications and design of products described in this literature without notice. John Deere, the leaping deer symbol, and John Deere's green and yellow trade dress are the trademarks of Deere & Company. Copyright 2023, Frontier Equipment.